

# Piggyback Filter & Regulators

Advanced Air System Technology™

Provides *Clean, Regulated Air*  
to Your Applications!



RT-FR250-G

- ✓ ¼" Filter with built-in 0-120 PSI regulator
- ✓ Comes with glass face chrome gauge
- ✓ Low Pressure Drop, flows to 30 scfm
- ✓ Can be wall mounted or panel nut mounted
- ✓ Low cost, high efficiency design
- ✓ Semi-automatic drain with manual override
- ✓ Filters to 5 micron
- ✓ Maximum pressure is 230 PSI
- ✓ Temperature range from 40° F to 120° F
- ✓ Optional mounting bracket available



RT-FR500-G

- ✓ ½" Filter with built-in 0-120 PSI regulator
- ✓ Comes with glass face chrome gauge
- ✓ Low Pressure Drop, flows to 80 scfm
- ✓ Can be wall mounted or panel nut mounted
- ✓ Low cost, high efficiency design
- ✓ Semi-automatic drain with manual override
- ✓ Filters to 5 micron
- ✓ Maximum pressure is 180 PSI
- ✓ Temperature range from 40° F to 120° F
- ✓ Optional mounting bracket available



Reading Technologies, Inc.  
Advanced Air System Technology™

1031F MacArthur Road Reading, PA 19605  
1 800-521-9200 Fax 610 372-1984  
Website <http://www.driair.com>

# Provides Clean Air at a **Low Cost!**



RT-FR250

- ✓ ¼" Air filter
- ✓ 5 micron replacable filter element
- ✓ Low pressure drop, flows to 30 scfm
- ✓ Can be wall mounted through slots in body
- ✓ Lightweight, high efficiency design is durable and rugged
- ✓ Semi-automatic drain with manual override
- ✓ Maximum pressure is 230 PSI
- ✓ Temperature range from 40°F to 120°F



RT-FR500

- ✓ ½" Air filter
- ✓ 5 micron replacable filter element
- ✓ Low pressure drop, flows to 80 scfm
- ✓ Can be wall mounted through slots in body
- ✓ Lightweight, high efficiency design is durable and rugged
- ✓ Semi-automatic drain with manual override
- ✓ Maximum pressure is 180 PSI
- ✓ Temperature range from 40°F to 120°F

